

Constant Current LED Driver



- Input Voltage: 90-264V
- High Efficiency, High PF, IP67 Design.
- Selectable constant current output (Custom on request)
- Full-Isolated, delivering 10W up to 300W of power.
- Short circuit, over temperature, over current and over voltage protection.
- 3/5 years warranty
- LED Constant current driver waterproof applied to outdoor LED light, such as LED Panel Light, LED down light, LED Street light, LED Ceiling, LED track lights, LED Flood lights, etc.



Typical Specifications

Model No.	Output power	Output voltage	Output current	PF	Efficiency	IP Grade	Size(L*W*H)
OTM-W42300	10W	30-42V	300mA	0.9	82%	IP65	66*36*23mm
OTM-W36600	20W	28-36V	600mA	0.9	86%	IP65	85*45*25mm
OTM-W36900	30W	28-36V	900mA	0.93	88%	IP65	150*40*30mm
OTM-W361200	40W	28-36V	1200mA	0.93	88%	IP65	150*40*30mm
OTM-W361500	50W	28-36V	1500mA	0.93	88%	IP65	150*40*30mm
OTM-W361800	60W	28-36V	1800mA	0.95	88%	IP67	134*64*40mm
OTM-W362400	80W	28-36V	2400mA	0.95	89%	IP67	154*64*40mm
OTM-W363000	100W	28-36V	3000mA	0.95	90%	IP67	180*64*40mm
OTM-W363400	120W	28-36V	3400mA	0.95	90%	IP67	180*64*40mm
OTM-W364500	150W	28-36V	4500mA	0.95	91%	IP67	211*64*40mm
OTM-W365000	180W	28-36V	5400mA	0.95	91%	IP67	218*64*45mm
OTM-W366000	200W	28-36V	6000mA	0.95	91%	IP67	218*64*45mm
OTM-W367000	250W	28-36V	7000mA	0.96	92%	IP67	246*88*47mm
OTM-W368000	300W	28-36V	8000mA	0.96	92%	IP67	246*88*47mm